


# Rockgard 3000 Pipeline Protection System For All Environments.



### Description:

Rockgard 3000 is an aggressively adhesive, laminate pipeline tape. It features excellent conformability, is ultra flexible, & has superb mechanical characteristics which afford protection in all environments.  
It is truly a class leader!

### Applications:

Anti-corrosion tape coating for pipelines, welded joints, and fittings. Ideal for buried pipelines using selected backfill and harsher backfills. Recommended as a joint coating for Yellow Jacket, FBE, Tri-laminate, Sintakote, and Ductile Iron coated pipes.

### Characteristics:

Waterproof, Ultra-flexible, Puncture resistant, Cold Applied.

### Application:


Please refer to Savcor for specific application procedures.

General Applications:

1. Surface must be clean, dry, smooth and free of irregularities. Minimum Surface preparation ST2, mechanical wire brushes etc.
2. Tape must not be applied at a temperature lower than +5°C
3. Brush or roller apply Savcor 360 Primer and allow to tack off.
4. When coating irregular weld joints and fittings, profile areas of potential voids under wrapping with Savcor 460 Bitumen Mastic Strip.
5. Peel back silicone release paper approx 200mm, and apply bitumen adhesive face to substrate and firm into place.
6. Ensuring tape is kept taught without stretching, spirally wrap the pipe with a minimum 55% overlap, removing release paper as you progress.
7. When starting a new roll of tape this should overlap the previous roll by 100m approx.
8. When wrapping is complete, the line should be inspected to ensure there are no voids under the coating.

### Data:

Backing/Reinforcement Thickness: 0.50mm  
 Adhesive Thickness: 1.00mm  
 Total Thickness: 1.5mm  
 Tensile Strength: Long 711 N/mm : Trans 923N/mm ASTM D638  
 Elongation: Long 66% Trans 99% ASTM D638  
 Puncture Resistance: 1214N ASTM E154  
 Adhesion to primed Steel 5.8N/mm  
 Cold Flexibility -40°C DIN 52123  
 CD Resistance:ASTM G38A,30 Days-<190 (Group B)  
 Roll Size: 50mm,100mm,150mm widths x 10 M Roll.  
 Other non-standard sizes available on request.



Vic/Tas/SA 03 9993 7500	NSW 02 9663 2322	NZ 09 414 5080	QLD/NT 07 3890 8533	WA 08 9248 8999
----------------------------	---------------------	-------------------	------------------------	--------------------

All written data and statements herein are provided in good faith and believed to be reliable and appropriate at the time of drafting this document. However it is given without implied or express guarantee. Potential uses are urged to trial and /or conduct conformity test of the product to deem its suitable in application for a particular end use prior to purchase.